



ROOFING TECHNOLOGY





Why do we need to care about roofs?

- Roof and membrane failures are the most often litigated parts of a building
- good detailing is paramount
- never use materials or systems that have not been “approved” or tested by a reputable agency

GENERAL ROOFING TERMS

FROM THE INTERNATIONAL LIBRARY OF TECHNOLOGY, 33C, 1909



It is important to be familiar with the general roofing terms regarding their general shape and configuration.

ROOFING TYPES:

THE TWO PRIMARY TYPES OF ROOFING WE MUST CONSIDER ARE **FLAT** AND **PITCHED**:

Flat roofs are those slope is **LESS THAN 1 in 4** and use waterproof membranes (also called Low Slope)

Pitched roofs have slopes of **1 in 4 or GREATER** and generally use shingles

Roof Type Selection

- Depends on building use
- Span
- Structural materials
- Need to shed water or snow
- Need to provide overhangs for shading
- Need to provide overhangs to protect the wall materials
- Need for insulation (and type of insulation to be used - batt vs foam/rigid)
- Incorporation of skylights or roof glazing

Common Fact

- Flat roofs are prone to leaking
- Leaks are difficult to find as the entry point for the leaking water is usually not near the point of apparent leakage
- Sloped roofs tend to stay watertight if properly built (pay attention to ice dams...)

Roof Insulation Types


- Insulation varies in its water resistance
- Can be quite permeable to air/vapour **or** act as an air barrier
- Batt types are air permeable
- Closed cell foams are air Impermeable
- SO...
- **Batt types must be ventilated**
- Closed cell foams need not be ventilated

Environmental Issues


| Insulation Material | R-value R/inch | Density lb/ft ³ | Emb. E MJ/kg | Emb. Carbon kgCO ₂ /kg | Emb. Carbon kgCO ₂ /ft ² •R | Blowing Agent (GWP) | Bl. Agent kg/kg foam | Blowing Agent GWP/bd-ft | Lifetime GWP/ft ² •R |
|---|----------------|----------------------------|--------------|-----------------------------------|---|-----------------------------------|----------------------|-------------------------|---------------------------------|
| Cellulose (dense-pack) | 3.7 | 3.0 | 2.1 | 0.106 | 0.0033 | None | 0 | N/A | 0.0033 |
| Fiberglass batt | 3.3 | 1.0 | 28 | 1.44 | 0.0165 | None | 0 | N/A | 0.0165 |
| Rigid mineral wool | 4.0 | 4.0 | 17 | 1.2 | 0.0455 | None | 0 | N/A | 0.0455 |
| Polyisocyanurate | 6.0 | 1.5 | 72 | 3.0 | 0.0284 | Pentane (GWP=7) | 0.05 | 0.02 | 0.0317 |
| Spray polyurethane foam (SPF) – closed-cell (HFC-blown) | 6.0 | 2.0 | 72 | 3.0 | 0.0379 | HFC-245fa (GWP=1,030) | 0.11 | 8.68 | 1.48 |
| SPF – closed-cell (water-blown) | 5.0 | 2.0 | 72 | 3.0 | 0.0455 | Water (CO ₂) (GWP=1) | 0 | 0 | 0.0455 |
| SPF – open-cell (water-blown) | 3.7 | 0.5 | 72 | 3.0 | 0.0154 | Water (CO ₂) (GWP=1) | 0 | 0 | 0.0154 |
| Expanded polystyrene (EPS) | 3.9 | 1.0 | 89 | 2.5 | 0.0307 | Pentane (GWP=7) | 0.06 | 0.02 | 0.036 |
| Extruded polystyrene (XPS) | 5.0 | 2.0 | 89 | 2.5 | 0.0379 | HFC-134a ¹ (GWP=1,430) | 0.08 | 8.67 | 1.77 |

1. XPS manufacturers have not divulged their post-HCFC blowing agent, and MSDS data have not been updated. The blowing agent is assumed here to be HFC-134a.


R-Value Comparison



R/RSI value per inch/25mm of various insulating materials



How Much Insulation?



More insulation is required in ceilings as hot air rises so there is more thermal loss in that direction.

| ZONE | | A | B | C | D |
|------------------------------|-----|------|------|------|------|
| Walls | RSI | 3.0 | 3.6 | 4.1 | 5.3 |
| | R | 17.0 | 20.0 | 23.0 | 30.0 |
| Basement walls | RSI | 3.0 | 3.0 | 3.0 | 3.0 |
| | R | 17.0 | 17.0 | 17.0 | 17.0 |
| Roof or ceiling | RSI | 4.5 | 5.6 | 6.7 | 9.0 |
| | R | 26.0 | 32.0 | 38.0 | 51.0 |
| Floor (over unheated spaces) | RSI | 4.7 | 4.7 | 6.7 | 9.0 |
| | R | 27.0 | 27.0 | 38.0 | 51.0 |

Courtesy Producer Member Thermo-Cell

<https://isolofoam.com/en/r-rsi-converter/>

Divide number by 25 to convert to RSI/mm

Batt Type Insulation

- Typical for Pitched Residential applications
- Most often laid on the ceiling of the attic leaving lots of ventilation space above





Can be installed in roll form or blown in loose (loose often for retrofit as easier)



Batt/loose Type Materials



Cellulose

Considered to be the most environmentally benign.



Fiberglass

- **Recycled Content:** About 20%
- **Method and form:** Batts are most common but it's available in rigid. Reasonably low impact in production; raw materials are abundant; it offers good R value and reasonably good soundproofing.
- **R value:** 2.9 - 3.8 per inch
- **Notes:** Fibres are volatile and installation can irritate the skin. Be sure to wear a mask, gloves and goggles. Make sure it is well installed- It doesn't perform well if compressed, and gaps around studs and headers can actually encourage **air convection causing heat loss**.
- Fibreglass is moisture sensitive and should not be installed where it will be exposed to moisture. Despite how commonly it can be found insulating foundation walls, it should never be installed against a cold concrete wall.



Some batt insulation comes with a backer paper to use for installation - the paper instead of a plastic vapour barrier.



Stone/rock/mineral Wool

- **Recycled Content:** there is a minimum of 75% industrial waste in stone wool insulation, often as high as 90%.
- **Method and form:** Batts or rigid panels, the batts are an excellent replacement for fiberglass. Stone wool can be more costly per batt but has a higher R value than fiberglass per inch; less health risks during installation; easier installation; it performs better for fire and sound and is less harmful to the environment.
- Stone wool in interior walls reduces sound between rooms and floors, as well as offering fire protection.
- **Below grade durability :** as the climate warms, termites are moving north into Canada. Termites love foam insulation but the fibers in stone wool cut them, so they leave it alone.
- **R value:** 4 per inch








When dense mineral wool is placed on a flat roof it must be in a protected position so that it doesn't get wet.



Roofing membrane is being installed over the dense/rigid rockwool insulation to protect it from moisture.



Polystyrene: Expanded (EPS) vs. Extruded (XPS)

- XPS (Extruded polystyrene) refers to the coloured solid foam panels you most often see on the outside of buildings under construction. It offers a higher density and higher R-value per inch than EPS (expanded polystyrene) but because of its lower cost, EPS offers more R-value per dollar spent.
- Manufacturers of XPS and EPS claim both products can be recycled, but a complete life cycle analysis shows EPS having a better overall environmental impact when compared to XPS, as EPS can be recycled in many more ways at the end of its usefulness.


Extruded Polystyrene Foam (XPS)

- **Recycled content:** Minimal at best.
- **Method and form:** Comes in panels, 2x8, 4x8 and other dimensions.
- **R value:** 5 per inch; RSI= 0.035/mm
- **Notes:** XPS acts as a vapour barrier and air barrier.
- **Blowing agents** are 1430 times worse than carbon dioxide, exponentially worse than EPS. For ecological reasons rather than performance, we recommend limiting its use when possible. A combination of polyethylene and EPS can offer the same vapour protection as XPS, more affordably and with significantly less impact on climate.
- XPS is durable and unharmed by moisture, so it works well below grade.



It's blue or pink, depends on the manufacturer.






XPS, though waterproof, is placed below the membrane here to protect it from UV radiation.



When XPS is placed above the membrane it must be ballasted to protect it from wind uplift.

Here you see a drainage board covered by a filter cloth to keep the ballast from creeping down to damage the roofing membrane.



XPS insulation comes in tapered boards for use on roofs to support drainage where a sloped structural deck is not desired.


Expanded Polystyrene Foam (EPS)

- Recycled content: Not very high.
- Method and form: Comes in panels, 2x8, 4x8 and other dimensions, with variable thicknesses.
- R value: 3.6 to 4.2 per inch; RSI= 0.025 - 0.030/mm
- Notes: EPS is the only commercially available foam insulation panel that is at all vapour permeable, which can be an advantage in some applications, as can those that are vapour impermeable.
- The common blowing agent for EPS is pentane gas, which is ozone safe but has a global warming potential (GWP) 7 times greater than carbon dioxide. This is significantly lower than other types of foam, so we recommend it as the preferred choice of foam whenever possible.
- Excellent for below grade applications, both inside and out. EPS is unharmed by moisture, and allows a certain amount of moisture to pass through it.





EPS comes in varying thicknesses and also in tapered slabs to assist in roof drainage.





EPS foam used on a roof, installed under the roofing membrane in a protected position.

Tapered slabs are used to create the slope to drain the roof, leaving the roof itself, flat.




Extruded Polystyrene Foam (XPS)

- **Recycled content:** Minimal at best.
- **Method and form:** Comes in panels, 2x8, 4x8 and other dimensions.
- **R value:** 5 per inch
- **Notes:** XPS acts as a vapour barrier and air barrier.
- **Blowing agents** are 1430 times worse than carbon dioxide, exponentially worse than EPS. For ecological reasons rather than performance, we recommend limiting its use when possible. A combination of polyethylene and EPS can offer the same vapour protection as XPS, more affordably and with significantly less impact on climate.
- XPS is durable and unharmed by moisture, so it works well below grade.



It's blue or pink, depends on the manufacturer.





XPS, though waterproof, is placed below the membrane here to protect it from UV radiation.



Pitched Roof Materials:

SHINGLES:

- asphalt, sawn wood, shakes, slate, clay tiles or concrete tiles

THATCH:

- bundles of leaves, reeds or grasses

ARCHITECTURAL SHEET METAL:

- lead, copper and terne (stainless steel or sheet steel) with flat or standing seams

Terne is an alloy coating that was historically made of lead and tin used to cover steel, in the ratio of 20% tin and 80% lead. Currently, lead has been replaced with the metal zinc and is used in the ratio of 50% tin and 50% zinc.



Traditional roofing types



Traditional
thatched roof





"old" vs. "new" slate




Slate is typically installed over wood slats rather than plywood sheathing.





The life span of an asphalt-shingle roof shingles is somewhere between 15 and 30 years, depending on the quality of the roofing shingles and the climate in your region. Wind can often cause as much damage as water, cold temperatures and sun.








FIGURE 13.42
Starting an asphalt shingle roof. Most building codes require the installation of a snow-melt barrier beneath the shingles at the eave in regions with cold winters. The most effective form of barrier is a 3-foot-wide (900-mm)

strip of modified bitumen sheet that replaces the lowest course of asphalt-saturated felt paper. The bitumen self-seals around the shanks of the roofing nails as they are driven through it.



Pitched Roof: Shingle Ridge Detail




Pitched Roof: Shingle Valley Detail



Keep the valley clear and easy for water to drain.


CLOSED CUT VALLEY

DIAGRAM 1




WOVEN VALLEY

DIAGRAM 2




OPEN VALLEY

DIAGRAM 3




STARTER COURSE

DIAGRAM 5




FOURTH COURSE

DIAGRAM 6




CEMENT APPLICATION

DIAGRAM 7




FASTENER LOCATIONS

DIAGRAM 4



HIP & RIDGE

DIAGRAM 8



Roof felt



Shingle line

Vent pipe flashing

Valley flashing

Drip edge

**Chimney base
flashing**




**Cap flashing (shown
bent upward)**

Mortar joints

Step flashing

Cap flashing

Base flashing




Asphalt flashing
details



A saddle is used to divert water around the chimney







Ice and water shield being installed at the bottom meter of a shingled roof. Note that it is lapped UNDER the roofing paper to promote drainage. This extra membrane is thicker and more durable than roofing paper and is meant to prevent water leakage due to "ice dams" at the end of the roof.

Eave protection against ice dams







Figure 5. Ice Damming

Ice Dams





Note:
insulation
missing in
this
diagram!!

So important
to watch for
technical
mistakes on
diagrams in
books!









Installing separate shingle products, rather than sheet goods.



Installation details for tile products.





Batten mounted steel roof.



Contemporary tile look roof with underlayment





Larger sheet product











MISSION TILES



SHINGLE TILES

FIGURE 13.47
Two styles of clay tile roofs. The mission tile has very ancient origins.

Pitched Roof: Clay Tiles



Vatican, Rome



Vatican, Rome



Summer Palace, Beijing, China





Forbidden City, Beijing, China



Historic housing, Beijing, China

How clay tiles are secured













FIGURE 13.50

Installing a flat-seam metal roof. The three diagrams at the bottom of the illustration show the three steps in creating the seam, viewed in cross section. The cleats, which fasten the roofing to the deck, are completely concealed when the roof is finished.


Metal Roof: Flat Seam



Step 1: Each pan is formed in the sheetmetal shop with folded edges.



Step 2: Sheet metal cleats interlock with the folded edges and are nailed to the deck. The cleat is folded back over the nail head to protect the pan.



Step 3: The next pan is interlocked with the first. When all pans are in place, the edges are beaten flat and soldered or sealed.


Metal Roof: Flat Seam





ArchitectureWeek.com

In projects such as Gehry's EMP in Seattle, the use of metal cladding blurs the distinction between what is the wall and what is the roof.








The Gehry Weisman Art Museum in Minneapolis used similar techniques for the stainless steel cladding panels.




The Gehry Weisman Art Museum in Minneapolis used similar techniques for the stainless steel cladding panels.




Although here you can see for the flat window ledge detail that a sealant has been used to prevent water penetration. NOT the best solution! Slope to drain is ALWAYS more reliable




Walt Disney Concert Hall, Frank Gehry



Section AA



5 METAL PANEL ASSEMBLY - TYPE 5
NOT TO SCALE



3 METAL PANEL ASSEMBLY - TYPE 3
NOT TO SCALE



Residences, Colorado, Daniel Libeskind



Denver Art Museum Residences, Daniel Libeskind





FIGURE 13.51
Installing an architectural standing-seam metal roof.

Metal Roof: Standing Seam



Metal Roof: Standing Seam







Traditional Quebec roofs (don't use shingles)



Contemporary Standing seam metal roof



Commercial systems come in very long panels that are able to be continuous from the top to the bottom of a roof, with no need for intermediate splices as in the earthquake style that is used by Gehry.



Insulation can be placed between roofing layers.





Retrofit of a commercial standing seam roof over an existing roof.





The long panels can be curved on site to fit onto curved roofs.



Contemporary terne-look roof in standing seam





FIGURE 13.52


Installing a batten-seam metal roof. The battens are tapered in cross section to allow for expansion of the roofing metal.

- Aluminum
- Zinc and galvanized steel
- Chromium
- Steel
- Stainless steel
- Cadmium
- Nickel
- Tin
- Lead
- Brass
- Bronze
- Copper

Metal Roof: Blocked Seam




Metal Roof: Block Seam




Toronto Zoo

3.

-  Insulation
-  Roof Sheet
-  Structural Roof Support
-  Air/Vapour Barrier
-  Thermal Barrier
-  Thermal Clip



4.



Insulation



Roof Sheet



Structural Liner



Air/Vapour Barrier



Thermal Barrier



Structural Roof Support



Thermal Clip



This is a metal roof with a snow dam at the edge. This is required to stop snow from sliding off the roof and on to the people below.



Snow guards at the edge of roofs



HOME DEPOT



ONTARIO'S HOME IMPROVEMENT

able

kitchens

Blinds

APPLY



CHARGE CARD

TODAY!



YOU FIND

W

Flat or Low Slope Roofs:

PRIMARY COMPONENTS:

- structural roof deck
- thermal insulation
- vapour retarder (and air barrier)
- waterproof membrane



Structural Roof Deck:

- must be designed to *minimize deflection* to reduce ponding and minimize drainage
- either **slope the roof deck** or **taper the insulation** to drain roof
- usual materials are:
 - plywood
 - wood decking
 - cast or hollow core concrete
 - steel decking(choice depends on building type, fire rating and primary structural system)




FIGURE 13.3

A low-slope roof with insufficient pitch to drain is subject to structural failure through progressive collapse, as demonstrated in this sequence of cross sections: (a) Water stands on the roof in puddles, causing slight deflections of the roof deck between supporting beams or joists. (b) If heavy rainfall continues, the puddles grow and join, and the accumulating

weight of the water begins to cause serious deflections in the supporting structural elements. The deflections encourage water from a broader area of the roof to run into the puddle. (c) As structural deflections increase, the depth of the puddle increases more and more rapidly, until the overloaded structure collapses.



Roof collapse in Poland due to excessive snow loading


Vapour Retarders for Low Slope Roofs:

- membrane in a protected membrane roof is also the vapour/air barrier
- other types of low slope roofs use two layers of asphalt saturated roofing felt bonded together and to the roof with hot asphalt
- polyethylene film not used as it melts
- situated on the warm side of the insulation

Thermal Insulation:

Can be installed in THREE positions:

- **BELOW** the deck (classic house attic scenario)
- **BETWEEN** the deck and the membrane
- **ABOVE** the membrane




A vented air space is mandatory when using batt insulation in a flat roof!!

If you use rigid polystyrene insulation (the blue kind) or a foamed in place closed cell type, no air space is necessary as it is waterproof.

Flat Roof: Insulation and Membrane Position

BETWEEN




ABOVE

Flat Roof: BUR (traditional) vs. Inverted (newer methodology)

Insulation BETWEEN Membrane and Deck:


Traditional location for insulation:

- use low density rigid panels to support the loads on the roof membrane without allowing puncture of membrane
- any water vapour trapped in insulation will cause deck to rot so use topside vents to relieve pressure




Insulation BETWEEN Membrane and Deck:


Extruded polystyrene insulation is used on roofs (often blue in colour) as it is not penetrable by water so cannot deteriorate due to water logging. It is sensitive to UV radiation so must be protected.



Loose Laid Ballasted
Single-Ply Membrane



Fully Adhered
Single-Ply Membrane




Mechanically Fastened
Single-Ply Membrane



Insulation ABOVE the Membrane:

“New” concept (post 1970) offering major advantages:

- membrane protected from extremes of heat and cold, is on the warm side of the insulation
- membrane protected from UV radiation
- membrane protected from puncture
- insulation must be extruded polystyrene foam board which is water resistant and covered with a filter layer to prevent migration of ballast




ROOFING MEMBRANES:

THREE PRIMARY TYPES:


- conventional (bituminous built up roofing or BUR)
- prefabricated sheets (single ply)
- cast in situ

Conventional: The Built Up Roof (BUR)


- constructed of 3 to 5 layers of bitumen impregnated felts, layered on the roof deck with heated asphalt
- may be located either over or under the rigid insulation
- top layer of gravel ballast to protect asphaltic materials or insulation from UV rays, and to weight roofing materials against wind uplift forces



BUR on steel decking: insulation below the membrane



BUR on concrete roof deck: insulation above the membrane



Flat Roof: fibre matt used to keep ballast away from insulation



Built up Roof
(BUR)



Built up Roof (BUR)



Prefabricated Sheets: Single Ply

THERMOPLASTIC SHEETS:

- PVC and blends
- EP (ethylene interpolymers)
- CPA (copolymer alloys)

ELASTOMERIC (SYNTHETIC) RUBBER SHEETS:

- vulcanized, EPDM or neoprene
- non vulcanized

MODIFIED bituminous SHEETS:

- polymer modifiers


PREFABRICATED SHEETS: Installation and Attachment

- require less on site labour
- less prone to cracking
- affixed to roof by:
 - adhesives
 - the weight of ballast
 - fasteners concealed in seams between the sheets
 - with ingenious mechanical fasteners that do not penetrate the membrane (if it is flexible enough...)

THERMOPLASTIC SHEETS:

PVC:

- commonly known as vinyl
- seams are sealed either by solvent welding or hot air welding
- may be laid loose, mechanically attached, adhered or used as a protected membrane
- This material is not very good for the environment





PVC Roof at Pearson International Airport

ELASTOMERIC (SYNTHETIC) RUBBER SHEETS:


Neoprene

- high performance synthetic rubber compound
- applied in sheets and joined with an adhesive
- vulnerable to UV rays so coated with a protective layer
- may be adhered, mechanically fastened or laid loose and ballasted
- can be used in a protected membrane roof


ELASTOMERIC (SYNTHETIC) RUBBER SHEETS: EPDM (ethylene propylene diene monomer):

- the most widely used material for single ply roofs
- low in cost
- synthetic rubber made in large sheets
- joined with adhesive, laid loose, adhered, mechanically fastened or used in a protected membrane roof







Loose laid, ballasted, membrane




Mechanically fastened membrane: bar type




Mechanically fastened with disc fasteners



1. Roll membrane over knobbed base plate




2. Roll and snap on white retainer clip



3. Snap and screw on threaded black cap

Disc fastener detail





EPDM flashing

EPDM - loose laid and ballasted



Mechanical fastening strips and an EPDM roof





Polymer Modified Bitumens:

- sheets of bituminous material to which polymeric compounds have been added to increase cohesion, toughness and resistance to flow
- reinforced with fibrous mats
- some self adhere, or loose laid or laid in hot asphalt
- seams sealed by torching or hot asphaltic adhesive





Rolls of
polymer
modified
bituminous
roofing
sheets



OCAD modified bitumenous membrane roofing ready for installation





This is the roofing membrane being installed on the top of the new OCAD addition.



This is a multi-ply installation. The black being the base layer and the grey the more durable top layer. The insulation is beneath the black layer.




Detail at parapet. Note water overflow opening.

Can you spot the overflow
opening??



There is the
overflow spout!





Cast in Situ Membranes:

HOT APPLIED RUBBERIZED ASPHALT

COLD APPLIED LIQUID COMPOUNDS

- various polymeric and bituminous materials

POLYURETHANE FOAM ROOF WITH PROTECTIVE
COATING

Fluid Applied Membranes:

- used primarily for domes, vaults and complex shapes
- applied with a roller or spray gun in several coats and cure to form a rubbery membrane
- used as a spray on waterproofing layer over sprayed on polyurethane foam insulation



Spray applied elastomeric membrane roofing



Spray applied elastomeric membrane roofing

REQUIREMENTS OF ROOFING MEMBRANES:



- tensile strength
- elongation
- crack bridging
- fatigue resistance
- thermal shock
- tear resistance
- abrasion resistance
- lap joint integrity
- static puncture
- impact resistance
- low temp. flexibility
- weatherability
- heat aging
- dimensional stability
- granule embedment

Requirements continued:

- membrane attachment
- flashing attachment
- materials compatibility
- wind uplift resistance

These requirements apply to conditions during manufacture, during installation and in the field in service.

Details



© buildingscience.com

*Adapted from Baker, M.; Roofs, 1980;
Courtesy National Research Council of Canada*

Figure 4: Parapet Water Management—Keep rainwater from getting into the top of them. Slope the top of them inward so they don't stain the building façade. Make sure there is a waterproof membrane under the coping. And always have drip edges—front and back—so they don't stain the building façade.

<https://www.buildingscience.com/documents/insights/bsi-050-parapets-where-roofs-meet-walls>




FIGURE 13.29
A conventional parapet design. The coping attachment and flashing are very labor intensive, and therefore costly.




Figure 13: The Masonry Parapet—The thing to note here is that the concrete deck is the air control layer so an additional one is not necessary. However, joints in the concrete deck need to be addressed for air control layer continuity.

<https://www.buildingscience.com/documents/insights/bsi-050-parapets-where-roofs-meet-walls>




Figure 15: The Cantilevered Mini Parapet—Notice that air control layer continuity is achieved by wrapping the membrane over the building corner and then constructing the cantilevered portion of the parapet over the top of this air seal.

<https://www.buildingscience.com/documents/insights/bsi-050-parapets-where-roofs-meet-walls>




Figure 14: The Balloon Framed Steel Stud Parapet— This is the ugliest parapet to get right. Notice the use of spray polyurethane foam, the high density stuff, to provide air control layer continuity across the balloon framed exterior steel stud wall. The spray foam is supported by horizontal bridging or metal blocking. This is a tricky thing to execute and, as such, we design into the upper parapet assembly a pathway for drying via diffusion to provide some performance redundancy.

<https://www.buildingscience.com/documents/insights/bsi-050-parapets-where-roofs-meet-walls>





FIGURE 13.33

A roof penetration for a plumbing vent stack. Notice how this and all the previous edge and penetration details for a flat roof use the curb, cant strip, and stripping to keep standing water away from the edge of the membrane.







FIGURE 13.27
A building separation joint in a low-slope roof. Large differential movements between the adjoining parts of the structure can be tolerated with this type of joint because of the ability of the flexible joint cover to adjust to movement without tearing. A two-ply base flashing seals the edge of the membrane.

Flat Roof: expansion joint detail



Flat Roof: area divider

